

Wt-22 and WT-23 **Compact Machine Torches**



These compact size torches are available in both water cooled and air cooled models. While physically the smallest of the machine torches they share many important features with the larger models.

- Front or rear loading of the tungsten electrode. No need to raise or move the torch assembly to load or remove the electrode. The electrode withdraws with the shaft assembly when removed from the rear.
- Tightening of the electrode is made with the large shaft knob at the rear of the torch assembly, or by removing nozzle at front end.
- The 14" Model B is ideal for mounting wire feed guides, arc controls or cameras.
- A good selection of front end parts are available including three sizes of gas lens collet bodies. The gas lens insures protection of the critical weld zone by eliminating turbulence in the shielding gas flow. The gas lens also allows greater electrode stick-out for access to tight areas.
- Both models are available with hose and cable assemblies of 3 ft., 121/2 ft. or 25 ft. lengths.
- All accessories and spare parts are interchangeable with the popular 9.20 series hand torches.

ORDERING INFORMATION

WT-22A	260 Amps	WT-23A	130 Amps	
Water Coole	ed Torch Package - 7" Long	Air Cooled	Torch Package - 7" Long	
WT-22A-3	7" Torch body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable and hose assembly, power block bracket and	WT-23A-3	7" Torch body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable assembly.	
WT-22A-12	cable cover. 7" Torch body assembly, barrel, shaft assembly, insulating boot,	WT-23A-12	7" Torch body assembly, barrel, shaft assembly, insulating boot, $12^{1\!\!/}2$ ft. power cable assembly.	
	$12\frac{1}{2}$ ft. power cable and hose assembly.	WT-23A-25	7" Torch body assembly, barrel, shaft assembly, insulating bo	
WT-22A-25	7" Torch body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable and hose assembly.		25 ft. power cable assembly.	
	Order cable cover to protect cable and hose assembly			

WT-22B	260	Amps
--------	-----	------

V	<i>Vater</i>	Cooled	Iorch	Package -	14"	Long
---	--------------	--------	-------	-----------	-----	------

	a rerent dendge . r _eeng
WT-22B-3	14" Torch body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable and hose assembly, power block bracket and cable cover.
WT-22B-12	14" Torch body assembly, barrel, shaft assembly, insulating boot, $12^{1/2}$ ft. power cable and hose assembly.
WT-22B-25	14" Torch body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable and hose assembly.
	Order cable cover to protect cable and hose assembly

Bracket Assembly Option

28-18	Water Cooled Torches
28-18B	Air Cooled Torches

Accessory Kit: AK-920 collet, collet body $^3/_{32}$, gas lens $^3/_{32}$, gas lens

gasket, 3 alumina nozzles #6, #7, #8; tungsten electrode ³/₃₂.

WT-23B 130 Amps

Air Cooled Torch Package - 14" Long

WT-23B-3 14" Torch body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable assembly. WT-23B-12 14" Torch body assembly, barrel, shaft assembly, insulating boot, 121/2 ft. power cable assembly. WT-23B-25 14" Torch body assembly, barrel, shaft assembly, insulating

boot, 25 ft. power cable assembly.

Additional items such as power cable adapters or hook-up kits may be required to complete your torch set-up.

WT-22, WT-23 MACHINE TORCH SPECIFICATIONS

Maximum Capacity, Water-cooled (ac-dcsp) 260 AMPS
Air-cooled (ac-dcsp)130 AMPS
Barrel Diameter
Overall Length
Model B -14 ⁷ / ₁₆ " (36.7cm)

Tungsten Capacity (All models)	
Maximum Tungsten Length	Model A - 7" (17.8cm)
	Model B - 14" (35.6cm)
Cooling Requirements (Water-cooled models)	

For more information contact your local welding supply distributor.



TEC WELDING PRODUCTS, Inc. P.O. Box 1870, San Marcos, CA 92079 USA (760) 747-3700 • Fax (760) 747-2121 www.tectorch.com www.weldtec.com

Copyright 1998, 1999, 2000-2016 TEC TORCH COMPANY WELDTEC® is a registered trademark of TEC Torch Company

WT-28 and WT-29 Mid-size Machine **Torches**



These mid-size torches are available in both water cooled and air cooled models. While physically smaller than the WT-27 models they share many important features.

- Front or rear loading of the tungsten electrode. No need to raise or move the torch assembly to load or remove the electrode. The electrode withdraws with the shaft assembly when removed from the rear.
- Tightening of the electrode is made with the large shaft knob at the rear of the torch assembly, or by removing nozzle at front end.
- The 14" Model B is ideal for mounting wire feed guides, arc controls or cameras on the torch barrel.
- A good selection of front end parts make these models extremely versatile. Two sizes of gas lens collet bodies insures protection of the critical weld zone by eliminating turbulence in the shielding gas flow. The gas lens also allows greater electrode stickout for access to tight areas.
- Both models are available with hose and cable assemblies of 3 ft., 121/2 ft. or 25 ft. lengths.
- All accessories and spare parts are interchangeable with the popular 17, 18, 26 series hand torches.

ORDERING INFORMATION

WT-28A	350 Amps	WT-29A	180 Amps
Water Coole	d Torch Package - 7" Long	Air Cooled 7	Torch Package - 7" Long
WT-28A-3	7" Torch body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable and hose assembly.	WT-29A-3	7" Torch body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable assembly.
WT-28A-12	$7^{\rm H}$ Torch body assembly, barrel, shaft assembly, insulating boot, $12^{1\!/2}$ ft. power cable assembly.	WT-29A-12	7" Torch body assembly, barrel, shaft assembly, insulating boot, $12^1\!\!/2$ ft. power cable assembly.
WT-28A-25	7" Torch body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable assembly.	WT-29A-25	7" Torch body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable assembly.
	Order cable cover to protect cable and hose assembly.		

** 1 200	000 / tilips	** 1 ZOD	1007111100
Water Coole	ed Torch Package - 14" Long	Air Cooled 7	Torch Package - 14" Lor
WT-28B-3	14" Torch body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable and hose assembly.	WT-29B-3	14" Torch body assembly, 3 ft. power cable assembly
WT-28B-12	14" Torch body assembly, barrel, shaft assembly, insulating boot, $12^{1/2}$ ft. power cable assembly.	WT-29B-12	14" Torch body assembly, 12½ ft. power cable asser
WT-28B-25	14" Torch body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable assembly.	WT-29B-25	14" Torch body assembly, 25 ft. power cable assemb
	Order cable cover to protect cable and hose assembly.		

Bracket Assembly Option

27-18	Water Cooled Torches
27-18A	Air Cooled Torches

Accessory Kit: AK-1718 contains; 3/32 collet, collet body, gas lens gasket,

3 nozzles, #6, #7, #8 and 3/32 electrode...

WT-29B **180 Amps**

Air Cooled To	orch Package - 14" Long
WT-29B-3	$14\mbox{"}$ Torch body assembly, barrel, shaft assembly, insulating boot, $3\mbox{ ft.}$ power cable assembly.
WT-29B-12	14" Torch body assembly, barrel, shaft assembly, insulating boot, $12{}^1\!/2$ ft. power cable assembly.
WT-29B-25	14" Torch body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable assembly.

Additional items such as power cable adapters or hook-up kits may be required to complete your torch set-up.

WT-28, WT-29 MACHINE TORCH SPECIFICATIONS

Maximum Capacity, Water-cooled (ac-dcsp) 350 AMPS	Tungsten Capacity (All models)
Air-cooled (ac-dcsp) 180 AMPS	Maximum Tungsten Length Model A - 7" (17.8cm)
Barrel Diameter	Model B - 14" (35.6cm)
Overall Length	Cooling Requirements 1 Qt./min. (1 L/min)
Model B -14 ⁷ / ₁₆ " (36.7cm)	(Water-cooled models)


WT-27 Heavy Duty **Machine Torches**

WeldTec's machine TIG torches are the most advanced designs of their kind. Designed to meet the needs of today's TIG welding professionals.

They are available in several sizes and styles, both water cooled and air cooled. Now you can specify the exact model that best suits your application.

These important features are common to all WT-27 models.

- Front or rear loading of the tungsten electrode. No need to raise or move the torch assembly to load or remove the electrode. The electrode withdraws with the shaft assembly when removed from the rear.
- Tightening of the electrode can be made with the ribbed sleeve at the nozzle end or by the shaft knob at the rear of the torch body.



- The collet body features an integral gas lens containing fine stainless screens which eliminate turbulence in the shielding gas flow. The collet body-gas lens assemblies are available for tungsten electrode sizes 1/16" (1,6mm) through 1/4" (6,4mm) diameters.
- All WT-27 models are available with hose and cable assemblies in 3 ft., 121/2 ft. or 25 ft. lengths.

WT-27A

 All accessories and spare parts are interchangeable with other similar industry brands.

ORDERING INFORMATION

Bracket Assembly Option

Water Cooled Torches

gas lens collet body, 1 #10 nozzle, 2 #12 nozzles, 1/8 electrode.

Air Cooled Torches Accessory Kit: AK-27-18 contains; 1/8 collet,

27-18

27-18A

WT-27AA Air Cooled To	200 Amps orch Package - 9" Long	WT-27BA Air Cooled To	200 Amps orch Package - 20" Long	WT-27CA Air Cooled To	200 Amps orch Package - 9" Long
WT-27AA-3	9" body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable assembly.	WT-27BA-3	20" body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable assembly.	WT-27CA-3	9" body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable assembly.
WT-27AA-12	9" body assembly, barrel, shaft assembly, insulating boot, 12½ ft. power cable assembly.	WT-27BA-12	20" body assembly, barrel, shaft assembly, insulating boot, 12½ ft. power cable assembly.	WT-27CA-12	9" body assembly, barrel, shaft assembly, insulating boot, 12½ ft. power cable assembly
WT-27AA-25	9" body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable assembly.	WT-27BA-25	20" body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable assembly.	WT-27CA-25	9" body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable assembly.
WT-27AW	500 Amps	WT-27BW	500 Amps	WT-27CW	500 Amps
Water Coole	d Torch Package - 9" Long	Water Cooled	d Torch Package - 20" Long	Water Cooled	d Torch Package - 9" Long
WT-27AW-3	9" body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable and hose as-	WT-27BW-3	20" body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable and hose assembly.	WT-27CW-3	9" body assembly, barrel, shaft assembly, insulating boot, 3 ft. power cable and hose assembly.
WT-27AW-12	sembly. 9" body assembly, barrel, shaft assembly, insulating boot, 12½ ft. power cable and hose	WT-27BW-12	20" body assembly, barrel, shaft assembly, insulating boot, 12½ ft. power cable and hose assembly, bracket assembly.	WT-27CW-12	9" body assembly, barrel, shaft assembly, insulating boot, 12½ ft. power cable and hose assembly.
WT-27AW-25	assembly. 9" body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable and hose assembly.	WT-27BW-25	20" body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable and hose assembly, bracket assembly.	WT-27CW-25	9" body assembly, barrel, shaft assembly, insulating boot, 25 ft. power cable and hose assembly.

Additional items such as power cable adapters or hook-up kits may be required to complete your torch set-up.

WT-27 MACHINE TORCH SPECIFICATIONS

Maximum Capacity, Water-cooled (ac-dcsp) 500 AMPS	Tungsten Capacity (All models)
Air-cooled (ac-dcsp)	Maximum Tungsten Length Model A - 7" (17.8cm)
Barrel Diameter	Model B - 18" (45.7cm)
Overall Length Model A - 9" (22.9cm)	Model C - 7" (17.8cm)
Model B - 20" (50.8cm)	Cooling Requirements 2 Qt./min. (1.9 L/min)
Model C - 9" (22.9cm)	(Water-cooled models)